

IN THE SPECIFICATION

Paragraphs [0007], [0012], [0013] and [0014] are amended to correct some typing errors and translation errors. Undersigned states that no new matter is added.

[0007] Referring to Figs. 1 and 2, an axial flow fan of the first embodiment according to the present invention includes a frame 11, a driving device 12 and fan blade part 13. The driving device 12 is fixedly attached to a support part 111 of the frame 11. ~~The driving device 12 and the fan blade part 13~~ includes a hub member and a plurality of fan blades 132 disposed around the hub member 12. The hub member 131 engages with the driving device 12.

[0012] Referring to Figs. 5 and 6, The the frames 11, 21 can be added with a shield member 3 to enclose the fan blades 132, 232 outside the frames 11, 21 and the fan blade parts 13, 23 as a safety-guards guard respectively. Further, there are following two ways for join the frames 11, 21 and the shields— shield member 3:

[0013] Referring to Fig. 5 again, the frames 11, 21 are made with the shield member 3 as a single unit, that is, the frames 11, 21 engage with the shield 3 during fabrication.

[0014] Referring to Fig. 6 again, the shield 3 is attached to the frames 11, 21 by way of built-up, that is, the shield 3 can be attached to the frames 11, 21 by way of screw fastening components 31.